



The Fidelux FSTRS Vandalproof Series features 22 gauge powder coated steel, tamperproof screws, lens securing flanges, and an IK08 impact-resistant lens

FSTRS Vandalproof Smart Stairwell Series

Product Description

Fidelux FSTRS Vandalproof Series of Smart Stairwell fixtures, available in 2, 4, and 8 foot lengths in various CCTs and wattages, are designed for applications requiring increased protection from vandalism and theft. Features include a high-impact lens and lens securing flanges, as well as tamperproof screws to prevent access to the internal driver and technology. The Fidelux unit is right for potential high abuse areas. Optional heavy-duty wireguards are also available.

The sleek, contemporary design will complement any application without sacrificing ruggedness. Perfect for all stairwells and passageways in commercial, industrial, retail, and multi-family environments.

FSTRS units feature industry-leading premium drivers with 12V auxiliary output for greater application flexibility.

Features & Benefits

- Class P LED driver
- 0-10V, 1-100% flicker-free dimming; Dim-to-off
- For step dimming occupancy sensor, see FSTRS Sensor series fixtures
- 12V auxiliary output from driver
- Available in 3000K, 3500K, 4000K and 5000K
- CRI >80
- Factory-installed emergency lighting option
- L70 >100,000 hrs
- 10 year warranty

Mounting

- Wall / Surface Mounting
- Suspended Mounting

Construction

- 22 gauge powder coated steel
- IK08 88% transmission frosted polycarbonate lens
- Tamperproof Screws
- Lens securing flanges

Listings

- ETL Damp Location
- DLC Premium*




IK08

RoHS COMPLIANT

Dimensions

ADA COMPLIANT



Lengths
24" / 48" / 96"

Performance Summary

Efficacy: up to: 134 lm/W

CRI: Up to 84

CCT: 3000K / 3500K / 4000K / 5000K

Operating Temp: -13F to 131F (-25°C to +55°C)

L70: 100,000+ Hours

Ordering Guide Example: FSTRS-4FT-40W-50K-VP

FSTRS					VP
Series	Length	Wattage	CCT	Controls	Security
FSTRS	2FT	20W 30W	30 (3000K) 35 (3500K) 40 (4000K) 50 (5000K)	0-10v Dimming (STD) <i>For step dimming occupancy sensor, see FSTRS Sensor series fixtures</i>	VP (Vandalproof) <i>See VP Security tool/bit in Options</i>
	4FT	18W*, 25W* 40W			
	8FT*	45W, 60W, 70W, 80W			

EM15-VPT-WG4

Emergency	Options
EM8 (2' units) EM15 (4' units) EM30 (8' units)	VPT (#8/32 Security tool/bit; order separately) WG(2, 4, 8) (Wire Guard; specify length) BP(2, 4, 8) (Back plate; specify length) SUK (3' Suspension Mount Kit)

*DLC Pending for 3500K 8' units

FSTRS Series Specification Summary

	2FT (20W)	2FT (30W)	4FT (18W)	4FT (25W)	4FT (40W)	8FT (45W)	8FT (60W)	8FT (70W)	8FT (80W)
Efficacy lm/W @ 5000K	134 lm/W	134 lm/W	134 lm/W	133 lm/W	134 lm/W	121 lm/W	131 lm/W	125 lm/W	124 lm/W
Wattage	20W	30W	18W	25W	40W	45W	60W	70W	80W
Lumens @ 3000K	2748	3781	2280	3200	5233	5854	7544	8863	10410
Lumens @ 3500K*	2770	3820	2300	3220	5270	5864	7556	8875	10423
Lumens @ 4000K	2810	3850	2320	3250	5320	5896	8104	9368	10328
Lumens @ 5000K	2870	3930	2370	3300	5410	5897	8102	9277	10766
CRI	84.1	84.3	84.6	84.4	84	84.2	84.4	84.1	84.3
THD @ 120VAC	22.5 %	21 %	23.3 %	22.1 %	21 %	22.3%	22.1%	21.6%	21%
Color Temperatures	3000K / 3500K / 4000K / 5000K					3000K / 4000K / 5000K			
Dimming	0-10V								
Input Voltage Options	100-277VAC								
Qualifications / DLC Primary Use	DLC Premium Stairwell and Passageway Luminaires; 8' 35K units pending								
Power Factor	.876	.883	0.894	0.877	.98				
Viewing Angle	180°								
L70 Lifespan (TM21)	100,000								
Ambient Working Temp	-13F to 131F (-25°C to +55°C)								
Max Dimensions (in)	24" x 4" x 3"		48" x 4" x 3"			96" x 4" x 3"			
Total Weight	3.5 lbs		5 lbs			15 lbs			
Limited Warranty	10 Yrs.								

Values are nominal *DLC Pending for 3500K 8' units

FSTRS Series Emergency Power Performance Summary

Fixture	18W Units	20W Units	25W Units	30W Units	40W Units	45W Units	60W Units	70W Units	80W Units
FSTRS-2FT-EM8		1148 lm		1048 lm					
FSTRS-4FT-EM15	1975 lm		1980 lm		2029 lm				
FSTRS-8FT-EM30						7177	5383	4614	4037 lm

Values are nominal